

IBM i
Version 7.2

*Availability
Maximum capacities*



IBM i
Version 7.2

*Availability
Maximum capacities*



Note

Before using this information and the product it supports, read the information in "Notices" on page 15.

This edition applies to IBM i 7.2 (product number 5770-SS1) and to all subsequent releases and modifications until otherwise indicated in new editions. This version does not run on all reduced instruction set computer (RISC) models nor does it run on CISC models.

This document may contain references to Licensed Internal Code. Licensed Internal Code is Machine Code and is licensed to you under the terms of the IBM License Agreement for Machine Code.

© Copyright IBM Corporation 2003, 2013.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Maximum capacities	1
What's new for IBM i 7.2	1
PDF file for Maximum capacities	2
Cluster limits	2
Communications limits	3
Database and SQL limits	5
File system limits	5
Journal limits	7
Save and restore limits	8
Security limits	9
Work management limits	9
Miscellaneous limits	10
Related information for Maximum capacities	12
Notices	15
Programming interface information	17
Trademarks	17
Terms and conditions	17

Maximum capacities

If you exceed system limitations, you might experience an application outage or a system outage. Avoid these types of outages by being aware of the maximum capacities and system limitations in advance.

- | System limitations can be difficult to predict. This topic collection can help you understand your system's maximum capacity. The tables in this topic collection itemize some of the capacity limitations and restrictions that can affect the availability of large systems and their applications. For example, an online application halts when the size of a file or the number of its members reaches the size limitation. These tables list the limits or maximum values for the current release. Some of these maximum values are different (lower) on previous releases. There are environments or configurations where the actual limit can be less than the stated maximum. For example, certain high-level languages can have more restrictive limits. These limits can range from a certain number of objects to memory limitations. Memory limitations are measured in megabytes (MB), gigabytes (GB), terabytes (TB), and petabytes (PB) where 1 MB equals 1 048 576 bytes, 1 GB equals 1 073 741 824 bytes, 1 TB equals 1 099 511 627 776 bytes, and 1 PB equals 1 125 899 906 842 624 bytes.
- | **Note:** The values listed in this topic collection represent theoretical limits, not thresholds or recommendations. Approaching some of these limits might degrade system performance. Therefore, practical limits might be lower, depending on system size, configuration, and application environment.

What's new for IBM i 7.2

Read about new or significantly changed information for the Maximum capacities topic collection.

Maximum capacities provides users and administrators with system limits for many IBM® i functions. The purpose of this information is to aid in planning and managing how system limits can affect your system operations.

Updated system limits

- | For 7.2, Cluster limits have been updated for monitored resource entries. See Cluster limits table in the Information Center.
- | For 7.2, Journal limits have been updated to reflect new system limits. See Journal limits table in the Information Center.
- | For 7.2, Security limits have been updated for amount of storage used by a single user profile. See Security limits table in the Information Center.
- | For 7.2, Miscellaneous limits have been updated to reflect new limits. See Miscellaneous limits table in the Information Center.

How to see what's new or changed

To help you see where technical changes have been made, this information uses:

- The ➤ image to mark where new or changed information begins.
- The ➜ image to mark where new or changed information ends.

In PDF files, you might see revision bars (|) in the left margin of new and changed information.

To find other information about what's new or changed this release, see the Memo to users.

PDF file for Maximum capacities

You can view and print a PDF file of this information.

- To view or download the PDF version of this document, select Maximum capacities.

Saving PDF files

To save a PDF on your workstation for viewing or printing:

- Right-click the PDF link in your browser.
- Click the option that saves the PDF locally.
- Navigate to the directory in which you want to save the PDF.
- Click **Save**.

Downloading Adobe Reader

You need Adobe Reader installed on your system to view or print these PDFs. You can download a free copy from the Adobe Web site (www.adobe.com/products/acrobat/readstep.html).

Related reference:

"Related information for Maximum capacities" on page 12

IBM Redbooks® publications, Web sites, and other information center topic collections contain information that relates to the Maximum capacities topic collection. You can view or print any of the PDF files.

Cluster limits

- The IBM i system limits for clusters include cluster software limits, and OptiConnect limits.

Table 1. Cluster software limits

Cluster software limits	Value
Maximum number of nodes in a cluster	128
Maximum number of nodes in a recovery domain in a cluster resource group	128
Maximum number of clusters that a node may be a member of	1
Maximum number of IP addresses per cluster node	2
Maximum number of data port IP addresses per recovery domain node	4
Maximum number of site names per device cluster resource group	2
Maximum number of configuration objects per cluster resource group ¹	256 or 200
Maximum number of application restarts	3
Maximum number of monitored resources in a cluster administrative domain	45 000

Notes:

- Only 256 configuration objects are allowed in a cluster resource group if TCP/IP addresses are IPv4 format.
Only 200 configuration objects are allowed in a cluster resource group if TCP/IP addresses are IPv6 format.

Table 2. OptiConnect (Option 23 of IBM i) limits

OptiConnect limits	Value
Maximum number of systems that can be connected using OptiConnect	64
Maximum number of logical connection paths that can be established between two systems using OptiConnect	16
Maximum number of OptiConnect open connections between any two systems using OptiConnect ¹	16 382
Maximum total number of active jobs on a system that can use OptiConnect ¹	262 135
Maximum number of TCP/IP subnets per system that can be configured to use OptiConnect ²	8

Notes:

- 1. An OptiConnect open connection is an active communications link between a job or task on one system and a job or task on another system. Using the WRKOPCACT command, you can determine the number of current open connections by adding the 'Users' count under the Client Statistics View to the Agents count under the Server Statistics View. With this command, you can view the jobs and tasks associated with individual OptiConnect open connections by selecting F14 (Jobs and Tasks). The PRTOPCJOB command could also be used to list OptiConnect jobs and tasks.
- 2. The following count as TCP/IP subnets:
 - Each OptiConnect TCP/IP interface with no associated local interface (ADDTCPIFC keyword LCLIFC(*NONE))
 - Each unique interface associated with an OptiConnect TCP/IP interface

Communications limits

The IBM i system limits for communications include general communications configuration limits, SNA limits, TCP/IP limits, and communications trace service tool limits.

Table 3. General communications configuration limits

General communications configuration limits	Value
Maximum number of communications configuration objects that can be in a varied on state ¹	Approximately 100 000
Recommended maximum number of devices that are allocated to a communications subsystem	250 to 300
Maximum number of device descriptions for display devices per subsystem ²	Approximately 74 000
Maximum number of virtual devices that can be specified as automatically configured (QAUTOVRT system value)	32 500 or *NOMAX
Maximum communications/LAN hardware capabilities	See Power Systems™ Technical Guide on the Redbooks Web site  .

Notes:

1. A maximum of 32 767 communications configuration objects can be varied online at initial program load (IPL) per communications arbiter system job (see QCMNARB system value).
2. Removing generic workstation types in workstation entries can help avoid this limit. For example, the *ALL workstation type allows the subsystem to allocate all of the valid workstations on the system. Note that WRKSTNTYP(*ALL) is the default for some IBM-supplied subsystem descriptions.

Table 4. SNA communication limits

SNA communication limits	Value
Maximum number of communication arbiters (maximum value of QCMNARB system value)	99
Maximum number of active sessions per APPC node	512
Maximum number of modes per APPC device (or APPN location) ¹	14
Maximum combined number of APPC devices (in any state) and APPN devices (in varied on state)	25 300
Maximum number of APPN intermediate sessions	9999
Maximum number of devices per APPC controller	254
Maximum number of switched lines per APPC controller	64
Maximum size of APPN local location list	476
Maximum size of APPN remote location list	1898
Maximum size of asynchronous network address list	294
Maximum size of asynchronous remote location list	32 000
Maximum size of retail pass-through list	450
Maximum size of SNA pass-through group	254

Note:

1. An APPN location refers to all the devices that have the same values for RMTLOCNAME, RMTNETID, and LCLLOCNAME.

Table 5. TCP/IP communication limits

TCP/IP communication limits	Value
Maximum number of interfaces per line	2048
Maximum number of interfaces per system	16 384
Maximum number of routes per system	65 535
Maximum number of ports for TCP	65 535
Maximum number of ports for UDP	65 535
Maximum TCP receive buffer size	8MB
Maximum TCP send buffer size	8MB
Maximum size of a transmission unit on an interface	16 388 bytes
Maximum number of TELNET server jobs	200
Maximum number of pass-through server jobs	100
Maximum number of TELNET server sessions	Maximum number of virtual devices
Default maximum number of socket and file descriptors per job ¹	200
Maximum number of socket and file descriptors per job	2 500 000
Maximum number of socket descriptors on the system	Approximately 46 420 000
Maximum size of database files for FTP	1 terabyte
Maximum size of integrated file system files for FTP	Amount of storage
Maximum number of simultaneous inbound connections for SMTP	Configurable using the CHGSMTPA command, the limit is the system resources

Table 5. TCP/IP communication limits (continued)

TCP/IP communication limits	Value
Maximum number of simultaneous outbound connections for SMTP	Configurable using the CHGSMTPA command, the limit is the system resources
Maximum number of MX records handled by MX resolver (Client) for SMTP	80
Maximum document size for SMTP	2.1 GB
Maximum number of active threads per HTTP server	9999
Maximum number of connections that can be displayed using WRKTCPSTS or NETSTAT commands	32 767
Maximum number of L2TP tunnels per system	200
Maximum number of calls per L2TP tunnel	200
Note: Default can be changed with DosSetRelMaxFH() - Change the Maximum Number of File Descriptors (see UNIX-Type APIs in the information center).	

Table 6. Communications trace service tool limits

Communications trace service tool limits	Value
Maximum amount of storage allocated for a single communications trace buffer	4 GB
Maximum total amount of storage allocated for all communications trace buffers	16 GB
Maximum record size when using the TRCTCPAPP trace tool for Host Server and DDM/DRDA Server	6000 bytes

Database and SQL limits

Several types of IBM i system limits are related to database and SQL.

To view the limits for the Structured Query Language (SQL), see SQL limits. These limits include identifier length limits, numeric limits, string limits, datetime limits, datalink limits, and database manager limits.

To view the limits for database file sizes, see Database file sizes. These limits include the number of bytes in a record, number of key fields in a file, number of physical file members in a logical file member, among others.

File system limits

This topic contains the values for the system limits that are related to file systems. They include limits on the number of documents in a folder, the size of a document, the size of a stream file, and others.

Table 7. File system limits

File system limits	Value
Maximum number of libraries in the system part of the library list	15
Maximum number of libraries in the user part of the library list ¹	250
Maximum number of objects in a library ⁶	Approximately 360 000

Table 7. File system limits (continued)

File system limits	Value
Maximum number of documents and folders in a user auxiliary storage pool (ASP)	349 000
Maximum number of documents and folders in a folder	65 510
Maximum size of a document	2 GB - 1
Maximum cumulative number of objects across the "root" (/), QOpenSys, and user-defined file systems of ASPs 1 through 32	2 147 483 647
Maximum cumulative number of objects across the user-defined file systems for each independent ASP	2 147 483 647
Maximum cumulative number of user-defined file systems in ASPs 1 through 32	2 147 483 647
Maximum number of user-defined file systems in an independent ASP	Approximately 4000
Maximum number of directories in one *TYPE1 directory in the "root" (/), QOpenSys, or user-defined file systems	32 765
Maximum number of directories in one *TYPE2 directory in the "root" (/), QOpenSys, or user-defined file systems	999 998
Maximum number of *TYPE1 directory links for an object in the "root" (/), QOpenSys, or user-defined file systems	32 767
Maximum number of *TYPE2 directory links for an object in the "root" (/), QOpenSys, or user-defined file systems	1 000 000
Maximum size of a stream file	Approximately 1 TB
Default maximum number of file and socket descriptors per job ²	200
Maximum number of file and socket descriptors per job	2 500 000
Maximum for directory levels, path names, and object attributes and links	See the File system comparison topic in the information center. See <code>Qp0lProcessSubtree()</code> --Process a Path Name and <code>QlgProcessSubtree()</code> --Process a Path Name (using NLS-enabled path name) for more information.
Maximum number of directory levels when processing objects within a subtree using the <code>Qp01ProcessSubtree()</code> and <code>QlgProcessSubtree()</code> APIs and most integrated file system commands	See Maximum number of file and socket descriptors per job in this table. See <code>Qp0lProcessSubtree()</code> --Process a Path Name and <code>QlgProcessSubtree()</code> --Process a Path Name (using NLS-enabled path name) for more information.
Maximum length (in bytes) of a path name when processing objects within a subtree using the <code>Qp01ProcessSubtree()</code> and <code>QlgProcessSubtree()</code> APIs and most integrated file system commands	16 773 116
Maximum number of directory (folder) levels when deleting a directory (folder) using IBM Navigator for i ⁵	300
Maximum number of directory (folder) levels when viewing a directory's (folder's) total data size and contents properties using IBM Navigator for i	300
Maximum number of files that the IBM i Access File Server can have open at one time ³	16 776 960
Maximum number of scan descriptors per job ⁴	Approximately 524 000

Table 7. File system limits (continued)

File system limits	Value
Notes:	
1.	There are compatibility considerations for application programs that retrieve library lists and are not prepared for the longer lists. For more details, see the 7.2 Memo to Users.
2.	Default can be changed with DosSetRelMaxFH() - Change the Maximum Number of File Descriptors (see UNIX-Type APIs in the information center.)
3.	This limit is cumulative across all file server jobs (QPWFSxxxx, QZLSFILE and QZLSFILET jobs) on the system. After a file is closed, it no longer counts toward the limit. Some applications that can be affected by this limit are IBM i Access, IBM i NetServer, Network Stationstartup (which keeps over 200 files open, unless using Compact Flash Memory, which only requires about 25 files) and applications, and the QFileSrv.400 file system.
4.	For more information about scan descriptors, see Integrated File System Scan on Open Exit Program in the API topic collection.
5.	The Remove Directory (RMVDIR) command with SUBTREE (*ALL) specified can be used to delete directories exceeding this limit. See Remove Directory (RMVDIR) for more information.
6.	This number can be less if the library contains objects of types *MODULE, *PGM, *QRYDFN, *SQLPKG or *SRVPGM because of internal space used by these objects.

Journal limits

Some IBM i system limits relate to journals, such as the size of a journal receiver, the length of a single journal entry, and the maximum sequence number for journal entries.

Table 8. Journal limits

Journal limits	Value
Maximum size of a single journal receiver	Approximately 1 terabyte
Maximum length of a single journal entry (bytes)	4 000 000 000 bytes
Maximum length of a single journal entry that can be written using the Send Journal Entry (QJOSJRNE) API	15 761 440 bytes
Maximum sequence number for journal entries	18 446 744 073 709 551 600
Maximum number of objects that can be associated with one journal ¹	10 000 000
Maximum number of objects allowed on a single APYJRNCHG or RMVJRNCHG command	10 000 000
Maximum number of journal receivers allowed in a range of receivers on a journal command	2 045
Maximum number of remote journal target systems for broadcast mode	255
Maximum number of active commitment definitions with object-level changes that can be processed concurrently by an APYJRNCHG or APYJRNCHGX command	32 767
Maximum number of journal receivers that can be associated with one journal	131 036

Note:

1. This maximum includes objects whose changes are currently being journaled, and journal receivers that are associated with the journal. If the number of objects is larger than this maximum, journaling does not start.

Save and restore limits

Some IBM i system limits relate to save and restore, such as limits for the size of a save file and the size of an object that can be saved.

Table 9. Save and restore limits

Save and restore limits	Value
Maximum number of related objects that can be saved or restored in a single save operation ¹	Approximately 111 000
Maximum number of related internal integrated file system objects that can be saved in a single operation ³	Approximately 500 000
Maximum number of names in a save or restore command specifying which objects or libraries to include or exclude in the save or restore operation ²	300
Maximum number of concurrent save or restore operations	Limited only by available machine resources
Maximum size of an object that can be saved	Approximately 2 TB
Maximum size of a save file ⁵	Approximately 2 TB
Maximum size of description data saved for a file or set of related files ^{1,4}	Approximately 4 GB

Notes:

1. All database file objects in a library that are related to each other by dependent logical files are considered to be related objects. Starting in V5R4, all database files in a library that have referential constraints are considered to be related objects when using the save-while-active function.
A database file object consists of one or more internal objects. A maximum of approximately 500 000 related internal objects can be saved in a single save operation. One internal object is saved for each database file object, along with the following additional internal objects:
 - If the physical file is not keyed, add 1 internal object per member.
 - If the physical file is keyed, add 2 internal objects per member.
 - If the physical file has unique or referential constraints, add 1 internal object per constraint.
 - If the physical file has triggers, add 1 internal object for the file.
 - If the physical or logical file has column level authorities, add 1 internal object for the file.
 - If you use ACCPTH(*YES) on the save command, add 1 internal object for each logical file in the save request.
2. Using generic names to specify groups of objects or libraries can help avoid this limit. For the LIB, OMITLIB and OMITOBJ parameters on save commands, you can use the Command User Space (CMDUSRSPC) parameter to raise the limit to 32 767 simple or generic names.
3. Example of related internal integrated file system objects are objects with multiple hard-coded links or Java programs attached to a stream file.
4. Description data includes descriptions of files, formats, fields, members, and access paths, as well as general object descriptions. It also includes intermediate source code such as that generated by the SQL precompiler or REXX interpreter. If your save operation exceeds this limit, you may need to save the data without saving logical file access paths, or you may need to omit some files or members and save them in a separate operation.
A limit of 16 MB per file remains in effect for 6.1 and earlier releases. Objects with more than 16 MB descriptive data cannot be saved to a target release of 6.1 or earlier.
5. A limit of 1 TB remains in effect for 5.4 and earlier releases. Save files larger than 1 TB cannot be transmitted to or restored on systems running 5.4 or earlier releases.

Security limits

Some IBM i system limits relate to security, such as limits on the length of passwords and the number of user profiles on a system.

Table 10. Security limits

Security limits	Value
Maximum number of entries for a user profile ^{1, 2, 3}	50 000 000
Maximum number of objects that can be secured by an authorization list	16 777 215
Maximum number of private authorities to an authorization list ⁴	49 999 999
Maximum number of entries in a validation list	549 755 813
Maximum number of user profiles on a system ⁶	Approximately 340 000
Maximum length of a password	128
Maximum number of profile handles in a job	Approximately 20 000
Maximum number of profile tokens on the system	Approximately 2 000 000
Maximum amount of storage in the system and basic user ASPs, or in each Independent ASP, for permanent objects owned by a single user profile ⁵	8 589 934 592 TB

Notes:

1. A user profile contains four categories of entries: 1) every object owned by the profile, 2) every private authority the profile has to other objects, 3) every private authority to objects owned by this profile that other profiles have, and 4) every object for which this profile is the primary group. The sum of these categories equals the total number of entries for the profile.
2. The operating system maintains internal user profiles that own objects that are shared or cannot be assigned to a single individual user (for example, QDBSHR owns shared database objects such as database formats, access paths, and so on). These internal user profiles are subject to the same limits as any other user profile on the system.
3. Using authorization lists or group profiles reduces the number of private authorities and helps avoid this limit (see the Security topic in the information center).
4. Limit is due to the maximum number of entries allowed for the user profile that owns the authorization list (one less because a category 01 entry is used for the ownership of the authorization list).
5. Limit is not enforced when the maximum storage attribute of the user profile is *NOMAX.
6. Since user profiles are stored in the QSYS library, this number can be less if the QSYS library contains objects of types *MODULE, *PGM, *QRYDFN, *SQLPKG or *SRVPGM because of internal space used by these objects.

Work management limits

There are IBM i system limits that are related to work management, such as limits on the number of jobs on a system, the number of active subsystems, and the number of jobs in a subsystem.

Table 11. Work management and spooled file limits

Work management and spooled file limits	Value
Maximum number of jobs on the system	970 000
Maximum number of active subsystems	32 767
Maximum number of jobs in a subsystem	32 767
Maximum number of prestart jobs initially started when subsystem started	9999

Table 11. Work management and spooled file limits (continued)

Work management and spooled file limits	Value
Maximum amount of temporary auxiliary storage that can be specified for a job	Approximately 2 PB or *NOMAX
Maximum number of active memory storage pools	64
Maximum number of spooled files per job	999 999
Maximum number of spooled files in the system and basic user ASPs	Approximately 2 610 000
Maximum number of spooled files in each independent ASP	Approximately 10 000 000
Maximum number of records for a printer file	2 147 483 647
Maximum page number that can be displayed for a spooled file using the DSPSPLF command ¹	9999
Maximum page count that can be displayed for a spooled file using the WRKSPLF, WRKOUTQ, or WRKJOB OPTION(*SPLF) command ²	99 999
Maximum number of writers that can be active at the same time	Approximately 43 600
Notes:	
1. If the page count exceeds 9999, the display still shows page number 9999. The IBM Navigator for i interface does not have this limitation and shows the correct page number.	
2. If the page count exceeds 99 999, then ++++++ is displayed instead. The IBM Navigator for i interface does not have this limitation and shows the correct page count.	

Miscellaneous limits

There are some other IBM i system limits, such as the number of basic disk pools, the size of a user space, and the size of a message queue.

Table 12. Miscellaneous limits

Miscellaneous limits	Value
Maximum system and I/O hardware configurations and capacities	See Power Systems Technical Guide.
Minimum load source size	70 GB
Maximum load source size	2 TB
Maximum number of disk arms that are contained in all of the basic auxiliary storage pools (ASPs 1 - 32), per partition	2 047
Maximum number of disk arms that are contained in all of the independent auxiliary storage pools (iASPs 33 - 255) in all nodes in a cluster	2 047
Minimum number of disk arms that are required for acceptable performance.	See Performance Papers and Articles in the Resource Library on the Performance Management  website.
Maximum number of connections to a logical unit or disk unit in an external storage server or Virtual I/O Server environment.	8
Maximum combined number of disk arms and redundant connections to a disk units	35 600
Maximum number of basic user ASPs	31
Maximum number of independent ASPs	223

Table 12. Miscellaneous limits (continued)

Miscellaneous limits	Value
Maximum number of logical partitions	See Logical partitions in the information center.
Maximum database size for Domino®	64 GB
Maximum size of a user space ¹	16 773 120 bytes
Maximum size of a user index ²	1 TB
Maximum size of a data queue or a user queue ³	2 GB
Maximum size of a message queue ⁴	16 MB (approximately 75 000 messages)
Maximum number of new messages of any one message type on a message queue	Limited only by size of message queue
Maximum number of program messages that can be created in a job ⁵	4 294 967 293
Maximum number of records for each version of the history log	10 000 000
Maximum number of unique Volume IDs displayed/printed in Product Activity Log's Removable Media Lifetime Statistics for each Media Option	5000
Maximum number of input fields that can be specified for a display file	256
Maximum total size of concurrently used terospace address ranges per job	Approximately 64 TB
Range of user-defined double-byte characters that can be defined and maintained using the character generator utility (CGU) for Japanese	Hexadecimal 6941 through 7FFE
Maximum memory per partition	16 TB
Minimum memory per partition	256 MB
Maximum number of processors per partition	32 processor cores on Power7 systems and earlier running with a maximum of SMT4. Can be expanded to 96 processor cores with IBM Lab Services arrangement.
Maximum partition ID	1000
Maximum number of LUNs or optical devices that are associated with a virtual SCSI adapter pair for IBM i	16
Maximum number of virtual target SCSI devices per virtual SCSI connection	16
Maximum number of storage volumes per virtual fiber channel connection (NPIV)	64
Maximum Virtual I/O Server configurations and capacities	See Specifications, Limitations, and Restrictions topics under "Planning for the Virtual I/O Server" in the IBM Power Systems Hardware Information Center.
Maximum number of workload capping groups	255
Maximum number of IMGCLG entries in a single IMGCLG	256
Maximum size of a virtual media	1 000 000 MB
Maximum number of virtual tape resources	35
Maximum number of virtual optical resources	35
Maximum number of active (varied on) optical devices	100

Table 12. Miscellaneous limits (continued)

Miscellaneous limits	Value
Maximum number of drives from a logical tape library can be attached to an IBM i partition	32
Maximum number of drives can be configured in a logical tape library attached to an IBM i partition	256
Maximum number of storage elements in one logical tape library	15 000
Notes:	
1. Listed size is the maximum when the machine is allowed to choose the alignment. Absolute maximum size of a user space is 16 776 704 bytes.	
2. To create a 1 TB capable user index when using the QUSCRTUI API, specify a value of 1 for the index size option. Otherwise, the size limit is 4 GB.	
3. The maximum size of a data queue that can be created through the data queue host server is 16 megabytes.	
4. Message queue QSYSOPR is shipped with a message queue full action of *WRAP. When the message queue is full, the oldest informational and answered messages are removed from the message queue to allow space for new messages to be added. If the removing of the informational and answered messages does not provide enough space, then unanswered inquiry messages are removed until there is space to add the new message. The default reply is sent before an unanswered inquiry message is removed. For more information, see the MSGQFULL parameter on the CHGMSGQ command.	
5. If the job has multiple threads, then the limit is the number of messages from all threads combined.	

Table 13. Interprocess Communication (IPC) limits

Interprocess Communication (IPC) limits	Value
Maximum number of Single UNIX Specification message queues on the system	2 147 483 646
Maximum size of a Single UNIX Specification message queue	16 773 120 bytes
Maximum size of a single message on a Single UNIX Specification message queue	65 535 bytes
Maximum number of semaphore sets on the system	2 147 483 646
Maximum number of semaphores per semaphore set	65 535
Maximum number of shared memory segments that can be created on the system	2 147 483 646
Maximum size of a teraspace shared-memory segment that is created by using the shmget() function	4 294 967 295 bytes
Maximum size of a teraspace shared-memory segment that is created by using the shmget64() function	17 450 452 123 648 bytes
Maximum size of a resizeable teraspace shared-memory segment	268 435 456 bytes
Maximum size of a nonteraspace shared-memory segment	16 776 960 bytes
Maximum size of a resizeable nonteraspace shared-memory segment	16 773 120 bytes

Related information for Maximum capacities

IBM Redbooks publications, Web sites, and other information center topic collections contain information that relates to the Maximum capacities topic collection. You can view or print any of the PDF files.

Web sites

- | • IBM i Maximum capacities 
- | Use this Web site to view information regarding system limits for 7.1.
- | • IBM i Maximum capacities 
- | Use this Web site to view information regarding system limits for 6.1.

Other information

- IBM i Clusters technology
- Getting started with System i® communications
- Files and file systems
- Journal management
- Backup and recovery
- Security
- Work management

Related reference:

“PDF file for Maximum capacities” on page 2

You can view and print a PDF file of this information.

Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
1623-14, Shimotsuruma, Yamato-shi
Kanagawa 242-8502 Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
Software Interoperability Coordinator, Department YBWA
3605 Highway 52 N
Rochester, MN 55901
U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Each copy or any portion of these sample programs or any derivative work, must include a copyright notice as follows:

© (your company name) (year). Portions of this code are derived from IBM Corp. Sample Programs.

© Copyright IBM Corp. _enter the year or years_.

Programming interface information

This Maximum capacities publication documents intended Programming Interfaces that allow the customer to write programs to obtain the services of IBM i.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other product and service names might be trademarks of IBM or other companies.

Terms and conditions

Permissions for the use of these publications is granted subject to the following terms and conditions.

Personal Use: You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative works of these publications, or any portion thereof, without the express consent of IBM.

Commercial Use: You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

IBM[®]

Product Number: 5770-SS1

Printed in USA